



Made in Germany

RAPIDTEST 38®

RAPIDTEST 38® serves to check if the treatment of polyolefins (polypropylene, polyethylene, polybutylene) has shown an effect onto the material. A stroke of the pen leaves a full line on the material if the material's surface tension has a value of 38 mN/m or more. If the material's surface tension is below 38 mN/m, the fluid contained in the pen will form small drops on the surface. The fluid applied to the surface will dry within seconds, it does not need to be wiped off anymore.

Ideal for testing
large film surfaces



RAPIDTEST 38®

Stroke width: 5 mm
Content: 5 ml
art. no. 40.66100.0



RAPIDTEST 38® JUMBO

Stroke width: 15 mm
Content: 15 ml
art. no. 40.66100.4



RAPIDTEST 38® Jumbo refillable

Stroke width: 30 mm
Content: 20 ml
art. no. 40.66100.5

- not harmful to the environment
- does not cause eye damage
- not harmful to health

RAPIDTEST 38® refill ink

Content: 22 ml
art. no. 40.66200.0



- Easy to handle
- Perfect for quick checks on polyolefins
- Smudge-proof and waterproof
- Colour-intensive, low-odour ink
- Ink colour: green
- The permanent display of the test result can be stored for quality assurance purposes



Safety data sheet:

ATTENTION: The test fluid of RAPIDTEST 38® contains solvent. This may attack solvent-sensitive materials (e.g. PS) and lead to the erroneous interpretation of test results!

Test pens should not be used if the surface is contaminated, as the residual contamination from the test surface can remain in the felt of the pens and falsify later values. For contaminated surfaces, use arcotest® test ink in bottles with arcotest® cotton swabs. Not suitable for metal surfaces.

Managing Director: Fritz P. Bloss
Amtsgericht Mannheim HRB 511684
IdNr. DE 813775094

arcotest GmbH
Rotweg 25
D-71297 Mönshheim
Germany

www.arcotest.info
E-mail: info@arcotest.info
Phone.: +49(0)7044 - 90 22 70
Fax: +49(0)7044 - 90 22 69

